

User authorization

Обновлено 11.06.2019

Содержание:

- General information
- User authorization
 - Method request
 - Request example
 - Description of parameters
 - Method response
 - Response example
 - Description of parameters
 - Error handling
 - Response example
- Closing the current session
 - Method request
 - Request example
 - Description of parameters
 - Method response
 - Response example
 - Description of parameters
- Data on the current session
 - Method request
 - Request example
 - Description of parameters
 - Method response
 - Response example for active session
 - Response example for expired session
 - Description of parameters

General information

This service allows you to perform the following actions:

1. To authorize user (to get session ID);
2. To close the current session;
3. To get data on the current session.

User authorization

Method request

Request example

Method address: <https://api.dellin.ru/v1/customers/login.xml>

```
<request>
  <appkey>00000000-0000-0000-0000-000000000000</appkey>
  <login>info@info.ru</login>
  <password>Password1</password>
</request>
```

Description of parameters

Request

Parameter	R*	Type	Description
appkey	Yes	string	Application key. To get the key, register
login	Yes	string	Login for personal account at dellin.ru
password	Yes	string	Password for personal account at dellin.ru

Method response

Response example

```
<response>
  <sessionid>00000000-0000-0000-0000-000000000000</sessionid>
</response>
```

Description of parameters

Response

Parameter	Type	Description
sessionID	string	Session ID for getting access to the API methods of the personal account at dellin.ru

Error handling

Response example

```
<response>
  <errors>Unauthorized</errors>
</response>
```

Closing the current session

Method request

Request example

Method address: <https://api.dellin.ru/v1/customers/logout.xml>

```
<request>
  <appkey>00000000-0000-0000-0000-000000000000</appkey>
  <sessionid>00000000-0000-0000-0000-000000000000</sessionid>
</request>
```

Description of parameters

Request

Parameter	R*	Type	Description
appkey	Yes	string	Application key. To get the key, register
sessionID	Yes	string	Session ID for getting access to the API methods of the personal account at dellin.ru

Method response

Response example

```
<response>
  <answer>ok</answer>
</response>
```

Description of parameters

Response

Parameter	Type	Description
answer	string	Status of the session closing

Data on the current session

Information about the status of the current session may be used for session resumption before sending a request to API of the personal account.

Method request

Request example

Method address: https://api.dellin.ru/v1/customers/session_info.xml

```
<request>
  <appkey>00000000-0000-0000-0000-000000000000</appkey>
  <sessionid>00000000-0000-0000-0000-000000000000</sessionid>
</request>
```

Description of parameters

Request

Parameter	R*	Type	Description
appkey	Yes	string	Application key. To get the key, register
sessionID	Yes	string	Session ID for getting access to the API methods of the personal account at dellin.ru

Method response

Response example for active session

```
<response>
  <session>
    <expire_time>2014-04-12 18:01:45</expire_time>
    <expired>false</expired>
  </session>
</response>
```

Response example for expired session

```
<response>
  <session>
    <expire_time></expire_time>
    <expired>true</expired>
  </session>
</response>
```

Description of parameters

Response

Parameter	Type	Description
session	object	Current session
expire_time	string	Expiration date and time of the current session
expired	boolean	Expiration indicator of the current session