

Available counterparties

Обновлено 26.06.2020

Содержание:

- General information
- Counterparties list
 - Method request
 - Request example
 - Description of parameters
 - Request
 - Method response
 - Response example
 - Description of parameters
 - Response
 - Counteragents
 - Balance
 - Shared
 - Error handling

General information

The service allows getting the list of counterparties with the access to the account.

Counterparties list

One account can be associated with several counterparties, that is, it possible to process orders, get information about the settlements and perform other actions on behalf of different counterparties from one account.

This method allows:

- getting basic information about counterparties that are associated with certain account;
- getting full information about counterparties that are associated with certain account;
- getting information on the cash flow for each counterparty;
- changing the current counterparty in the personal account.

Method request

Request example

Method address: <https://api.dellin.ru/v2/counteragents.json>

```
{
  "appkey": "00000000-0000-0000-0000-000000000000",
  "sessionId": "00000000-0000-0000-0000-000000000000",
  "cauid": "00000000-0000-0000-0000-000000000000",
  "fullInfo": true
}
```

Description of parameters

Request

Request

Parameter	Required	Type	Description
appkey	Yes	string	Application key. To get the key, register
sessionId	Yes	string	To get the session ID, use the User Authorization method
cauid	No	string	UID of the counterparty that needs to be chosen in order to perform operations on its behalf during the current session. The parameter allows changing the default counterparty to another one.

fullInfo	No	boolean	Flag for requesting detailed information as well as the information on the cash flow for each counterparty
----------	----	---------	--

Method response

Response example

```
{
  "metadata":{
    "status":200,
    "generated_at":"2015-06-18 12:37:28"
  },
  "data":{
    "counteragents":[
      {
        "balance":{
          "opening":{
            "date":"2016-04-01 00:00:00",
            "sum":380
          },
          "closing":{
            "date":"2016-04-30 23:59:59",
            "sum":0
          }
        },
        "info":{
          "sharedTo":[
            {
              "phone":"+7 (111) 111-11-11",
              "name":"ООО",
              "email":"Pushkino_auto@dellin.ru"
            },
            {
              "phone":"+7 (444) 444-44-44",
              "name":"ООО",
              "email":"Petr.Petrov@dellin.ru"
            }
          ],
          "accessLevel":2,
          "requestComment":null,
          "managerEmail":"Ivan.Ivanov@dellin.ru",
          "managerPhone":"+7 (911) 232-95-50",
          "sharedFrom":{
            "phone":"+7 (111) 111-11-11",
            "name":"ООО",
            "email":"ssidorov@dellin.ru"
          },
          "managerName":"Иванов Иван Иванович"
        },
        "isCurrent":true,
        "uid":"00000000-0000-0000-0000-000000000000",
        "juridical":true,
        "inn":"1234567890",
        "document":{
          "type":"passport",
          "serial":"0000",
          "number":"123456"
        },
        "name":"ООО \"Компания\"",
        "cashOnDeliveryAvailable":true
      }
    ]
  }
}
```

Description of parameters

Response

Parameter	Type	Description
metadata	object	System information
— metadata.status	integer	Emulated status http-code. If successful, code 200 is returned
— metadata.generated_at	string	Server response date and time. Format: YYYY-MM-DD HH:MM:SS
data	object	Counterparties data
— data.counteragents	array of Counteragents	Array of available counterparties

Counteragents

Response.Counteragents

Parameter	Type	Description
-----------	------	-------------

balance	object	Counterparty cash flow. If no settlements were made, the parameter value is "null". The parameter is present in the response only if "" parameter with value "true" was passed in the request
— balance.opening	Balance	Counterparty balance at the beginning of the period
— balance.closing	Balance	Counterparty balance at the end of the period (or the current date, if period is not over)
info	object	Full information about the counterparties. The parameter is present in the response only if "" parameter with value "true" was passed in the request
— info.sharedTo	array of Shared	Information about the users with the access to the account
— info.accessLevel	integer	<p>Current access level.</p> <p>Possible values:</p> <ul style="list-style-type: none"> • 0 = access request in process; • 1 = access denied; • 2 = full access; • 3 = partial access <div style="border: 1px solid orange; padding: 10px; margin-top: 10px;"> <p>⚠ To get full access, confirm the account in the personal cabinet of Delovye Linii company website (send a copy of your passport or application) or come to the company terminal</p> </div>
— info.requestComment	string	Comment (in case the access has been denied)
— info.managerEmail	string	Client manager email
— info.managerPhone	string	Client manager phone number
— info.sharedFrom	Shared	Information about the user who has granted access to the personal account
— info.managerName	string	Client manager full name
isCurrent	boolean	<p>Selected counterparty flag.</p> <p>If request contained parameter "cauid", then in the response the "isCurrent" parameter value for the counterparty whose UID was passed in the request will be "true"</p>
uid	string	Counterparty UID
juridical	boolean	Flag indicating that counterparty is a legal entity (not an individual)
inn	string	TIN (taxpayer identification number) - for legal entities, if counterparty is an individual ("juridical" parameter value is "false"), then the parameter value is "null"
document	object	Identification document data - for individuals, if counterparty is a legal entity ("juridical" parameter value is "true"), then the parameter value is "null"
— document.type	string	<p>Document type.</p> <p>Possible values:</p> <ul style="list-style-type: none"> • "passport"; • "drivingLicence"; • "foreignPassport" - international passport
— document.serial	string	Document series
— document.number	string	Document number. Number format may vary depending on the country
name	string	Counterparty name
cashOnDeliveryAvailable	boolean	Flag indicating that cash on delivery type of payment is available to counterparty

Balance

Balance

Parameter	Type	Description
date	string	Period beginning/end date Format: YYYY-MM-DD HH:MM:SS
sum	integer	Amount at the period beginning/end, rubles

Shared

Shared

Parameter	Type	Description
phone	string	User phone number
name	string	User full name
email	string	User email

Error handling

The common API errors are used with the method, for errors format description and errors list see [Errors of API methods](#).