

Contact details

Обновлено 24.05.2018

Содержание:

- General information
- [Getting the list of contact persons and phone numbers](#)
 - [Method request](#)
 - [Request example](#)
 - [Description of parameters](#)
 - [Method response](#)
 - [Response example](#)
 - [Description of parameters](#)
- Contact persons adding and editing
 - [Contact person adding](#)
 - [Method request](#)
 - [Request example](#)
 - [Description of parameters](#)
 - [Method response](#)
 - [Response example](#)
 - [Description of parameters](#)
 - [Error handling](#)
 - [Response example](#)
 - [Contact person editing](#)
 - [Method request](#)
 - [Request example](#)
 - [Description of parameters](#)
- [Phone numbers adding and editing](#)
 - [Phone number adding](#)
 - [Method request](#)
 - [Request example](#)
 - [Description of parameters](#)
 - [Method response](#)
 - [Response example](#)
 - [Description of parameters](#)
 - [Error handling](#)
 - [Response example](#)
 - [Response example](#)
 - [Phone number editing](#)
 - [Method request](#)
 - [Request example](#)
 - [Description of parameters](#)

General information

This service allows you to get the list of contact persons and phone numbers, add and edit information in the list. Adding contact persons and phone numbers is available only for counterparties that are not anonymous receivers.

Getting the list of contact persons and phone numbers

Method request

Request example

Method address: <https://api.dellin.ru/v1/customers/book/address.json>

```
{
  "apikey": "00000000-0000-0000-000000000000",
  "sessionID": "00000000-0000-0000-0000-000000000000",
  "addressID": "1"
}
```

Description of parameters

Request

Parameter	R*	Type	Description
appkey	Yes	string	Application key. To get the key, register
sessionID	Yes	string	To get the session ID, use the User Authorization method
addressID	Yes	string	ID of address on which the list of contact persons and phone numbers is required

Method response

Response example

```
[
  {
    "contacts": [
      {
        "id": "1",
        "contact": "Иван Иванович Иванов"
      },
      {
        "id": "3",
        "contact": "Петр"
      }
    ],
    "lastUpdate": "2017-05-18T17:23:58.000+03:00",
    "phones": [
      {
        "id": "123",
        "phone": "79002350122",
        "phoneFormatted": "+7 (900) 235-01-22",
        "addNumber": "55677"
      },
      {
        "id": "321",
        "phone": "375127789955",
        "phoneFormatted": "+375 (12) 778-99-55"
      },
      {
        "id": "456",
        "phone": "495778999999999999",
        "addNumber": "0890"
      }
    ]
  }
]
```

Description of parameters

Response

Parameter	Type	Description
contacts	array of Response.Contacts	Array of contact persons
phones	array of Response.Phones	Array of phone numbers
lastUpdate	string	Date of information last update

Response.Contacts

Parameter	Type	Description
id	string	Contact person ID
contact	string	Contact person full name

Response.Phones

Parameter	Type	Description
id	string	Phone number ID
phone	string	Phone number (not formatted)
phoneFormatted	string	Phone number (formatted). It's missing if it is impossible to format it by international standard
addNumber	string	Extension phone number

Contact persons adding and editing

Contact person adding

Method request

Request example

Method address: <https://api.dellin.ru/v1/customers/book/contacts/update.json>

```
{
  "apikey": "00000000-0000-0000-000000000000",
  "sessionID": "00000000-0000-0000-0000-000000000000",
  "addressID": "4",
  "contact": "Иван"
}
```

Description of parameters

Request

Parameter	R*	Type	Description
apikey	Yes	string	Application key. To get the key, register
sessionID	Yes	string	To get the session ID, use the User Authorization method
addressID	Yes	string	ID of address for which addition of the contact person is required
contact	Yes	string	Contact person full name

Method response

Response example

```
{
  "success": {
    "addressID": "4",
    "personID": "244"
  }
}
```

Description of parameters

Response

Parameter	Type	Description
success	object	Information about the added contact person
— success.addressID	string	ID of address for which addition of the contact person is done
— success.personID	string	ID of added contact person

Error handling

In case of errors, response will contain the names of parameters that caused errors with errors description. Error description in example below: "required parameter is not passed".

Response example

```
{
  "errors": {
    "contact": "не передано обязательное поле"
  }
}
```

Contact person editing

Method request

Request example

Method address: <https://api.dellin.ru/v1/customers/book/contacts/update.json>

```
{
  "apikey": "00000000-0000-0000-000000000000",
  "sessionID": "00000000-0000-0000-0000-000000000000",
  "personID": "244",
  "contact": "Иван Иванович"
}
```

Description of parameters

Request

Parameter	R*	Type	Description
apikey	Yes	string	Application key. To get the key, register
sessionID	Yes	string	To get the session ID, use the User Authorization method
personID	Yes	string	ID of contact person that needs to be edited
contact	Yes	string	New contact person full name

✓ Responses of method when adding and editing contact person are similar.

Phone numbers adding and editing

Phone number adding

Method request

Request example

Method address: <https://api.dellin.ru/v1/customers/book/phones/update.json>

```
{
  "apikey": "00000000-0000-0000-000000000000",
  "sessionID": "00000000-0000-0000-0000-000000000000",
  "addressID": "4",
  "phoneNumber": "+7 (900) 235-01-22",
  "addNumber": "0867"
}
```

Description of parameters

Request

Parameter	R*	Type	Description
apikey	Yes	string	Application key. To get the key, register
sessionID	Yes	string	To get the session ID, use the User Authorization method
addressID	Yes	string	ID of address for which addition of the phone number is required
phoneNumber	Yes	string	Phone number
addNumber	No	string	Extension phone number. Maximum length - 5 symbols

Method response

Response example

```
{
  "success": {
    "addressID": "4",
    "phoneID": "214"
  }
}
```

Description of parameters

Response

Parameter	Type	Description
success	object	Information about the added phone number
— success.addressID	string	ID of address for which addition of the contact person is done
— success.phoneID	string	Phone number ID

Error handling

In case of errors, response will contain the names of parameters that caused errors with errors description. Error description in example below: "required parameter is not passed".

Response example

```
{
  "errors":{
    "phoneNumber":"не передано обязательное поле"
  }
}
```

When trying to add a phone number for anonymous receiver, you will get the following error message. Error description in example below: "Adding of phone numbers for simplified shipping counterparties is prohibited".

Response example

```
{
  "errors":{
    "phoneNumber":"Запрещено добавление телефонных номеров для адреса контрагента по упрощённой отправке"
  }
}
```

Phone number editing

Method request

Request example

Method address: <https://api.dellin.ru/v1/customers/book/phones/update.json>

```
{
  "appkey": "00000000-0000-0000-000000000000",
  "sessionID": "00000000-0000-0000-0000-000000000000",
  "phoneID": "214",
  "phoneNumber": "+7 (900) 235-01-22",
  "addNumber": "0867"
}
```

Description of parameters

Request

Parameter	R*	Type	Description
appkey	Yes	string	Application key. To get the key, register
sessionID	Yes	string	To get the session ID, use the User Authorization method
phoneID	Yes	string	ID of phone number that needs to be edited
phoneNumber	Yes	string	New phone number
addNumber	No	string	New extension phone number. Maximum length - 5 symbols

✓ Responses of method when adding and editing phone numbers are similar.