

Other methods of address book

Обновлено 11.06.2019

Содержание:

- General information
- Deletion of objects from the address book
 - Method request
 - Request example
 - Description of parameters
 - Method response
 - Response example
 - Description of parameters

General information

This service allows you to perform other actions with address book that are not described in other sections.

Deletion of objects from the address book

Method request

Request example

Method address: <https://api.dellin.ru/v1/customers/book/delete.xml>

```
<request>
  <appkey>00000000-0000-0000-0000-000000000000</appkey>
  <sessionId>00000000-0000-0000-0000-000000000000</sessionId>
  <counteragents>
    <id>123</id>
    <id>345</id>
  </counteragents>
  <addresses>
    <id>3</id>
    <id>2</id>
    <id>1</id>
  </addresses>
  <phones>
    <id>1</id>
    <id>2</id>
  </phones>
  <contacts>
    <id>1</id>
    <id>2</id>
    <id>3</id>
  </contacts>
</request>
```

Description of parameters

Request

Parameter	R*	Type	Description
appkey	Yes	string	Application key. To get the key, register
sessionID	Yes	string	To get the session ID, use the User Authorization method
counteragents	No	object	Information about the counterparties that need to be deleted
— counteragents.id	No	array of integer	Array of ID's of counterparties that need to be deleted
addresses	No	object	Information about the addresses that need to be deleted
— addresses.id	No	array of integer	Array of ID's of addresses that need to be deleted
phones	No	object	Information about the phone numbers that need to be deleted

— phones.id	No	array of integer	Array of ID's of phone numbers that need to be deleted
contacts	No	object	Information about the contact persons that need to be deleted
— contacts.id	No	array of integer	Array of ID's of contact persons that need to be deleted

Method response

Response example

```
<response>
  <deleted>
    <counteragents>123</counteragents>
    <counteragents>345</counteragents>
    <addresses>3</addresses>
    <addresses>2</addresses>
    <addresses>1</addresses>
    <contacts>1</contacts>
    <contacts>2</contacts>
    <contacts>3</contacts>
    <phones>1</phones>
    <phones>2</phones>
  </deleted>
</response>
```

Description of parameters

Response

Parameter	Type	Description
deleted	object	Information about deleted objects
— deleted.counteragents	array of integer	Array of ID's of deleted counterparties
— deleted.addresses	array of integer	Array of ID's of deleted addresses
— deleted.contacts	array of integer	Array of ID's of deleted contact persons
— deleted.phones	array of integer	Array of ID's of deleted phone numbers