

Other directories

Обновлено 16.07.2019

Содержание:

- General information
- [Directory of legal forms of organization](#)
 - [Method request](#)
 - [Request example](#)
 - [Description of parameters](#)
 - [Method response](#)
 - [Response example](#)
 - [Description of parameters](#)
- [Directory of order statuses](#)
 - [Method request](#)
 - [Request example](#)
 - [Description of parameters](#)
 - [Method response](#)
 - [Response example](#)
 - [Description of parameters](#)
- [Directory of parameters for statistics report](#)
 - [Method request](#)
 - [Request example](#)
 - [Description of parameters](#)
 - [Method response](#)
 - [Response example](#)
 - [Description of parameters](#)
- [Documents for receipt of cargo](#)
 - [Method request](#)
 - [Request example](#)
 - [Description of parameters](#)
 - [Method response](#)
 - [Response example](#)
 - [Description of parameters](#)
- [Nature of cargo](#)
 - [Method request](#)
 - [Request example](#)
 - [Description of parameters](#)
 - [Method response](#)
 - [Response example](#)
 - [Description of parameters](#)

General information

This service allows you to get data from other directories that are not mentioned in other sections.

Directory of legal forms of organization

This directory contains the list of legal forms of organization.

Method request

Request example

Method address: https://api.dellin.ru/v1/public/opf_list.json

```
{  "apikey": "0000000-0000-0000-0000-000000000000"}
```

Description of parameters

Request			
Parameter	R*	Type	Description
appkey	Yes	string	Application key. To get the key, register

Method response

Response example

```
{
  "hash": "1707aea20f301fd0a8787b5a68608dd6cf270347ea04c266f1b4c6aa540088a4",
  "url": "https://api.dellin.ru/catalog/opf_list.csv?sk=Kn00tWJcumDYUqRjtCEvhg&e=1401285434"
}
```

Description of parameters

Response

Parameter	Type	Description
hash	string	File hash code (MD5). By comparing the hash codes of two files received at different times, you can understand whether the data in the directory has changed or not
url	string	<p>Link to the file with directory data in csv format in utf-8 encoding (the link is valid for 10 minutes). The line delimiter in the file is the character "\n", the column delimiter is comma (","), and the text delimiter is the quotation mark (" ").</p> <p>The file contains the next columns:</p> <ul style="list-style-type: none"> • UID — unique identifier; • name — short name of legal form of organization ("ООО", "ОАО", etc.); • juridical — flag of juridical party ("1" - yes, "0" - no); • fullName — full name of legal form of organization; • innLength — number of digits in TIN; • countryUID — unique country identifier.

Directory of order statuses

Method request

Request example

Method address: <https://api.dellin.ru/v1/public/statuses.json>

```
{
  "appkey": "00000000-0000-0000-0000-000000000000"
}
```

Description of parameters

Request			
Parameter	R*	Type	Description
appkey	Yes	string	Application key. To get the key, register

Method response

Response example

```
{
  "hash": "db090d4a0111cc5a7a2282716218840972a65251651a4fb2dc8f6ea34e5d2fa0",
  "url": "https://api.dellin.ru/catalog/statuses.json?sk=0k92VHh-Am_cUX6qsvdEjQ&e=1496046122"
}
```

Description of parameters

Response

Parameter	Type	Description
hash	string	File hash code (MD5). By comparing the hash codes of two files received at different times, you can understand whether the data in the directory has changed or not
url	string	Link to the file with directory data in json format

Directory of parameters for statistics report

Method request

Request example

Method address: https://api.dellin.ru/v1/public/report_params.json

```
{  "appkey": "00000000-0000-0000-0000-000000000000"}
```

Description of parameters

Request			
Parameter	R*	Type	Description
appkey	Yes	string	Application key. To get the key, register

Method response

Response example

```
{  "hash": "0dd17e7c6e8e69455360f392577356ace95385b0a94f5a062ef07aeee46be4a0",  "url": "http://api.dellin.stage/catalog/report_params.csv?sk=5iq56DseyHlaqmY07atEpw&e=1506409060"}
```

Description of parameters

Response

Parameter	Type	Description
hash	string	File hash code (MD5). By comparing the hash codes of two files received at different times, you can understand whether the data in the directory has changed or not
url	string	<p>Link to the file with directory data in csv format in utf-8 encoding (the link is valid for 10 minutes). The line delimiter in the file is the character "\n", the column delimiter is comma (","), and the text delimiter is the quotation mark (" ").</p> <p>The file contains the next columns:</p> <ul style="list-style-type: none">• name — parameter name (key; in Latin);• caption — parameter name (in Cyrillic)

Documents for receipt of cargo

This directory contains the list of documents for receipt of cargo.

Method request

Request example

Method address: https://api.dellin.ru/v1/public/documents_for_receive.json

```
{  "appkey": "00000000-0000-0000-0000-000000000000"}
```

Description of parameters

Request

Parameter	R*	Type	Description
apikey	Yes	string	Application key. To get the key, register

Method response

Response example

```
{
  "hash": "1707aea20f301fd0a8787b5a68608dd6cf270347ea04c266f1b4c6aa540088a4",
  "url": "https://api.dellin.ru/catalog/documents_for_receive.csv?sk=Kn00tWJcumDYUqRjtCEvhg&e=1401285434"
}
```

Description of parameters

Response

Parameter	Type	Description
hash	string	File hash code (MD5). By comparing the hash codes of two files received at different times, you can understand whether the data in the directory has changed or not
url	string	<p>Link to the file with directory data in csv format in utf-8 encoding (the link is valid for 10 minutes). The line delimiter in the file is the character "\n", the column delimiter is comma (","), and the text delimiter is the quotation mark (" ").</p> <p>The file contains the next columns:</p> <ul style="list-style-type: none">• UID — unique identifier;• name — name of the document for receipt cargo;• day_to_day — flag indicating the possibility of receiving cargo on the same day using this document.

Nature of cargo

This directory contains the list of types of nature of cargo.

Method request

Request example

Method address: https://api.dellin.ru/v1/public/freight_types.json

```
{
  "apikey": "00000000-0000-0000-0000-000000000000"
}
```

Description of parameters

Request

Parameter	R*	Type	Description
apikey	Yes	string	Application key. To get the key, register

Method response

Response example

```
{
  "hash": "1707aea20f301fd0a8787b5a68608dd6cf270347ea04c266f1b4c6aa540088a4",
  "url": "https://api.dellin.ru/catalog/freight_types.csv?sk=Kn00tWJcumDYUqRjtCEvhg&e=1401285434"
}
```

Description of parameters

Response

Parameter	Type	Description
hash	string	File hash code (MD5). By comparing the hash codes of two files received at different times, you can understand whether the data in the directory has changed or not
url	string	<p>Link to the file with directory data in csv format in utf-8 encoding (the link is valid for 10 minutes). The line delimiter in the file is the character "n", the column delimiter is comma (","), and the text delimiter is the quotation mark (" ").</p> <p>The file contains the next columns:</p> <ul style="list-style-type: none">• UID — unique identifier;• description — name of the nature of cargo.