

Orders for shipping from the public part

Обновлено 22.06.2020

Содержание:

- [General information](#)
- [Order for shipping](#)
 - [Method request](#)
 - [Request example](#)
 - [Description of parameters](#)
 - [Request](#)
 - [DeliveryType](#)
 - [Package](#)
 - [AcDoc](#)
 - [Derival](#)
 - [PickupParams](#)
 - [Address](#)
 - [Arrival](#)
 - [Requester](#)
 - [Member](#)
 - [Counteragent](#)
 - [ContactPerson](#)
 - [PhoneNumber](#)
 - [DataForReceipt](#)
 - [Cargo](#)
 - [Method response](#)
 - [Response example](#)
 - [Description of parameters](#)
 - [Response](#)
 - [Data](#)
 - [Error handling](#)

General information

This service allows ordering/pre-ordering (see below) shipping without authorization (from the public part).

On creating orders with data of your personal account, see the relevant [section](#).

Below is the description of all method parameters, for the requests and the responses examples see the relevant [section](#).



Pre-order If a client wants to bring the cargo to the company terminal, they may place an order online, print the paper and bring it to the terminal. Thus they will be able to save time since the clients who placed a pre-order are served out of turn. For more information see Delovye Linii company [website](#).

Order for shipping

Method request

Request example

Method address: <https://api.dellin.ru/v2/request.xml>

```
<request>
  <apikey>00000000-0000-0000-0000-000000000000</apikey>
  <delivery>
    <deliveryType>
      <type>avia</type>
      <payer>sender</payer>
    </deliveryType>
    <packages>
      <uid>0xA0A820F33B2F93FE44C8058B65C77D0F</uid>
      <payer>sender</payer>
    </packages>
    <packages>
      <uid>0x947845D9BDC69EFA49630D8C080C4FBE</uid>
      <payer>sender</payer>
      <count>3</count>
    </packages>
  </delivery>
</request>
```

```

</packages>
<accompanyingDocuments>
  <action>send</action>
  <payer>sender</payer>
</accompanyingDocuments>
<accompanyingDocuments>
  <action>return</action>
  <payer>sender</payer>
</accompanyingDocuments>
<derival>
  <produceDate>2018-02-15</produceDate>
  <pickupParams>
    <derivalDriverPass>24</derivalDriverPass>
    <shipmentRegister>true</shipmentRegister>
    <paidEntry>
      <cost>100</cost>
      <type>1</type>
    </paidEntry>
    <shipmentDerival>A51000222</shipmentDerival>
    <priorCall>true</priorCall>
    <noNeedAgreement>true</noNeedAgreement>
    <documentsForReceive>0x90bc42c2d8cf7c1c47a40fc1ccfb54d5</documentsForReceive>
    <documentsForReceive>0x9c65f346435836584a8345ade132df00</documentsForReceive>
  </pickupParams>
  <variant>terminal</variant>
  <payer>sender</payer>
  <terminalID>23</terminalID>
  <address>
    <street>78000000000438000000000</street>
    <house>4</house>
    <building>3</building>
    <structure>лит.А</structure>
    <flat>214a</flat>
  </address>
  <additionalAddress>
    <address>
      <street>78000000000438000000000</street>
      <house>4</house>
      <building>3</building>
      <structure>лит.А</structure>
      <flat>214a</flat>
    </address>
    <payer>sender</payer>
  </additionalAddress>
  <time>
    <worktimeStart>09:00</worktimeStart>
    <worktimeEnd>18:00</worktimeEnd>
    <breakStart>12:30</breakStart>
    <breakEnd>13:30</breakEnd>
    <exactTime>true</exactTime>
  </time>
  <handling>
    <freightLift>true</freightLift>
    <toFloor>10</toFloor>
    <carry>50</carry>
    <payer>third</payer>
  </handling>
  <requirements>0x9951e0ff97188f6b4b1b153dfde3cfec</requirements>
  <requirements>0xabb9c63c596b08f94c3664c930e77778</requirements>
</derival>
<arrival>
  <variant>terminal</variant>
  <payer>sender</payer>
  <terminalID>23</terminalID>
  <city>770000000000000000000000</city>
  <address>
    <street>78000000000438000000000</street>
    <house>4</house>
    <building>3</building>
    <structure>лит.А</structure>
    <flat>214a</flat>
  </address>
  <time>
    <worktimeStart>09:00</worktimeStart>
    <worktimeEnd>18:00</worktimeEnd>
    <breakStart>12:30</breakStart>
    <breakEnd>13:30</breakEnd>
    <exactTime>true</exactTime>
  </time>
  <handling>
    <freightLift>true</freightLift>
    <toFloor>10</toFloor>
    <carry>50</carry>
    <payer>third</payer>
  </handling>
  <requirements>0x9951e0ff97188f6b4b1b153dfde3cfec</requirements>
  <requirements>0xabb9c63c596b08f94c3664c930e77778</requirements>
</arrival>
<smsback>79213332211</smsback>
<comment>комментарий к отправке</comment>
</delivery>
<members>
  <requester>
    <role>sender</role>
    <email>test@mail.ru</email>
  </requester>
  <sender>
    <counteragent>
      <form>0x8F51001438C4D49511DBD774581EDB80</form>
      <customForm>
        <formName>0БПΥΓ</formName>
        <countryUID>0x00000000000000000000000000000000</countryUID>
        <juridical>true</juridical>
      </customForm>
      <document>
        <type>passport</type>
        <serial>0000</serial>
        <number>123456</number>
      </document>
      <name>Ромашка</name>
      <inn>1234567890</inn>
    </sender>
  </members>

```

```

    <juridicalAddress>
      <street>78000000000438000000000</street>
      <house>4</house>
      <building>2</building>
      <structure>3A</structure>
      <flat>Б-234</flat>
    </juridicalAddress>
  </counteragent>
  <contactPersons>
    <name>Иван Иванович</name>
  </contactPersons>
  <phoneNumbers>
    <number>79213332211</number>
    <ext>0123</ext>
  </phoneNumbers>
  <email>test@mail.ru</email>
  <dataForReceipt>
    <send>true</send>
    <phone>+79999999999</phone>
    <email>test@mail.ru</email>
  </dataForReceipt>
</sender>
<receiver>
  <counteragent>
    <form>0x8F51001438C4D49511DBD774581EDB80</form>
    <customForm>
      <formName>ОБПУГ</formName>
      <countryUID>0x00000000000000000000000000000000</countryUID>
      <juridical>true</juridical>
    </customForm>
    <document>
      <type>passport</type>
      <serial>0000</serial>
      <number>123456</number>
    </document>
    <isAnonym>false</isAnonym>
    <phone>79998887766</phone>
    <name>Помашка</name>
    <inn>1234567890</inn>
    <juridicalAddress>
      <street>7800000000004380000000000</street>
      <house>4</house>
      <building>2</building>
      <structure>3A</structure>
      <flat>Б-234</flat>
    </juridicalAddress>
  </counteragent>
  <contactPersons>
    <name>Иван Иванович</name>
  </contactPersons>
  <phoneNumbers>
    <number>79213332211</number>
    <ext>0123</ext>
  </phoneNumbers>
  <email>test@mail.ru</email>
  <dataForReceipt>
    <send>true</send>
    <phone>+79999999999</phone>
    <email>test@mail.ru</email>
  </dataForReceipt>
</receiver>
<third>
  <counteragent>
    <form>0x8F51001438C4D49511DBD774581EDB80</form>
    <customForm>
      <formName>ОБПУГ</formName>
      <countryUID>0x00000000000000000000000000000000</countryUID>
      <juridical>true</juridical>
    </customForm>
    <document>
      <type>passport</type>
      <serial>0000</serial>
      <number>123456</number>
    </document>
    <name>Помашка</name>
    <inn>1234567890</inn>
    <juridicalAddress>
      <street>7800000000004380000000000</street>
      <house>4</house>
      <building>2</building>
      <structure>3A</structure>
      <flat>Б-234</flat>
    </juridicalAddress>
  </counteragent>
  <contactPersons>
    <name>Иван Иванович</name>
  </contactPersons>
  <phoneNumbers>
    <number>79213332211</number>
    <ext>0123</ext>
  </phoneNumbers>
  <email>test@mail.ru</email>
  <dataForReceipt>
    <send>true</send>
    <phone>+79999999999</phone>
    <email>test@mail.ru</email>
  </dataForReceipt>
</third>
</members>
<cargo>
  <quantity>1</quantity>
  <length>0.42</length>
  <width>0.18</width>
  <height>0.3</height>
  <weight>25</weight>
  <totalVolume>0.02</totalVolume>
  <totalWeight>0.02</totalWeight>
  <oversizedWeight>25</oversizedWeight>
  <oversizedVolume>0.02</oversizedVolume>
  <hazardClass>2.1</hazardClass>
  <insurance>
    <statedValue>11220.5</statedValue>

```

```

<payer>sender</payer>
<term>true</term>
</insurance>
<freightUID>0x9c2acaea110d75ba48fdc7a83c976269</freightUID>
<freightName>Запчасти для трактора</freightName>
</cargo>
<payment>
  <type>cash</type>
  <primaryPayer>sender</primaryPayer>
  <paymentCity>780000000000000000000000</paymentCity>
</payment>
</request>

```

Description of parameters

Request

Request

Parameter	Required	Type	Description
Root parameters			
appkey	Yes	string	The application key. To get the key, register
delivery	Yes	object	Delivery parameters
— delivery.deliveryType	Yes	DeliveryType	Delivery type for terminal-to-terminal shipping
— delivery.packages	No	array of Package	List of required packages
— delivery.accompanyingDocuments	No	array of AcDoc	Accompanying documents
— delivery.derival	Yes	Derival	Delivery from the address
— delivery.arrival	Yes	Arrival	Delivery to the address
— delivery.smsback	No	string	Phone number for SMS-notifications. Format: "7XXXXXXXXXX" (11 figures, starts with 7)
— delivery.comment	No	string	Comment to the order. Maximum field length: 500 characters
members	Yes	object	Shipping members
— members.requester	Yes	Requester	Order requester
— members.sender	Yes	Member	Sender
— members.receiver	Yes	Member	Receiver
— members.third	No	Member	Third party
cargo	Yes	Cargo	Cargo characteristics
payment	Yes	object	Payment parameters
— payment.type	Yes	string	Payment type. Available values: <ul style="list-style-type: none"> "cash" - by cash or credit card; "noncash" - by bank transfer
— payment.primaryPayer	Yes	string	Default payer. Specified party pays for the main service (terminal-to-terminal shipping) and all other services, unless other payers are specified for them. Available values: <ul style="list-style-type: none"> "sender"; "receiver"; "third"

— payment.paymentCity	No*	string	<p>CLADR code of the city. It's possible to get CLADR code using the services presented on the page "Using CLADR codes".</p> <p>(CLADR - Classifier of Addresses of Russian Federation)</p> <p>*Parameter is required if one of payers is the third party</p>
-----------------------	-----	--------	---

DeliveryType

DeliveryType			
Parameter	Required	Type	Description
type	Yes	string	<p>Delivery type.</p> <p>Available values:</p> <ul style="list-style-type: none"> • "auto" (by truck); • "express"; • "letter"; • "avia"; • "small" (small-size cargo) <div> <p>Small size cargo is the cargo with parameters that do not exceed the following values:</p> <ul style="list-style-type: none"> • weight is less than or equal to 10 kg; • LWH is less than or equal to 0.54*0.39*0.39 m; • volume is less than or equal to 0.1 cubic meters. <p>It is only possible to order Small Cargo Delivery service if there are Delovye Linii company terminals in the city of departure and city of arrival. For more information see company website.</p> </div>

payer	No	string	<p>Payer for the service.</p> <p>Available values:</p> <ul style="list-style-type: none"> • "sender"; • "receiver"; • "third" (third party). <p>If parameter is not passed, then it takes the value of the parameter "Request.Payment.primaryPayer"</p>
-------	----	--------	--

Package

Package			
Parameter	Required	Type	Description
uid	Yes	string	Package UID from "Directory of Additional Services"

payer	No	string	<p>Payer for the service.</p> <p>Available values:</p> <ul style="list-style-type: none"> • "sender"; • "receiver"; • "third" (third party). <p>If parameter is not passed, then it takes the value of the parameter "Request.Payment.primaryPayer"</p>
count	No*	integer	<p>Number of bags or boxes.</p> <p>Parameter is required if the package "bag" ("Упаковка мешок") or "carton box" ("Картонная коробка") is selected</p>

AcDoc

AcDoc

Parameter	Required	Type	Description
action	Yes	string	<p>Action over accompanying documents.</p> <p>Available values:</p> <ul style="list-style-type: none"> • "send"; • "return"
payer	Yes	string	<p>Payer for the service.</p> <p>Available values:</p> <ul style="list-style-type: none"> • "sender"; • "receiver"; • "third" (third party). <p>If parameter is not passed, then it takes the value of the parameter "Request.Payment.primaryPayer"</p>

Derival

Derival

Parameter	Required	Type	Description
produceDate	Yes	string	<p>Date of cargo transfer to the terminal of departure or date of truck arrival to the sender.</p> <p>Format: YYYY-MM-DD</p>
pickupParams	No	PickupParams	Additional parameters of cargo delivery from the address
variant	Yes	string	<p>Shipping method.</p> <p>Available values:</p> <ul style="list-style-type: none"> • "terminal" - delivery from the terminal; • "address" - delivery from the address. <p>If delivery from the address is ordered, then the order is placed, if delivery from the terminal - then pre-order.</p> <p>If small-size cargo delivery is ordered ("delivery.deliveryType.type" request parameter value is "small"), then delivery from the terminal is not available</p>

payer	No	string	<p>Payer for the service.</p> <p>Available values:</p> <ul style="list-style-type: none"> • "sender"; • "receiver"; • "third" (third party). <p>If parameter is not passed, then it takes the value of the parameter "Request.Payment.primaryPayer"</p>
terminalID	Yes*	integer	<p>Terminal ID from the "Terminals" directory.</p> <p>In case of express delivery ("delivery.deliveryType.type" request parameter value is "express") the terminal should accept express cargoes (there should be "Worktables.Worktable.department" parameter with "Приём груза к экспресс-перевозке" value for the selected terminal in Terminals directory).</p> <p>*It's possible to pass only one of parameters: "terminalID", "address"</p>
address	Yes*	Address	<p>Address as a set of parameters.</p> <p>*It's possible to pass only one of parameters: "terminalID", "address"</p>
additionalAddress	No	object	Picking up the cargo at an additional address
— additionalAddress.address	No	Address	Address as a set of parameters
— additionalAddress.payer	No	string	<p>Payer for the service.</p> <p>Available values:</p> <ul style="list-style-type: none"> • "sender"; • "receiver"; • "third" (third party). <p>If parameter is not passed, then it takes the value of the parameter "Request.Payment.primaryPayer"</p>
time	Yes*	object	<p>Time of cargo picking up.</p> <p>*Parameter is required only if specified shipping method is "address"</p>
— time.worktimeStart	Yes	string	<p>Beginning of period of cargo picking up.</p> <p>Format: HH:MM</p>
— time.worktimeEnd	Yes	string	<p>End of period of cargo picking up.</p> <p>Format: HH:MM</p>
— time.breakStart	No	string	<p>Beginning of the break.</p> <p>Format: HH:MM</p>
— time.breakEnd	No	string	<p>End of the break.</p> <p>Format: HH:MM</p>
— time.exactTime	No	boolean	<p>Picking up at the exact time.</p> <p>Default value: "false"</p>
handling	No	object	Loading and unloading works at the address
— handling.freightLift	No	boolean	<p>There is a freight elevator.</p> <p>Default value: "false"</p>
— handling.toFloor	No	integer	<p>Number of the floor.</p> <p>Maximum number of characters - 5</p>

— handling.carry	No	integer	The distance of carrying the load manually. Maximum number of characters - 5
— handling.payer	No	string	Payer for the service. Available values: <ul style="list-style-type: none"> • "sender"; • "receiver"; • "third" (third party). If parameter is not passed, then it takes the value of the parameter "Request.Payment.primaryPayer"
requirements	No	array of string	Array of UID's of special requirements for transport from the Directory of Special Requirements for Transport . Special requirements include type of truck loading (side, rear, etc.) and other requirements: manipulator, tenting removal, etc.

PickupParams

PickupParams

Parameter	Required	Type	Description
derivalDriverPass	No	integer	Parameter determining the need to order a pass by the driver of DL to enter the territory of the sender and time that it takes. Available values: <ul style="list-style-type: none"> • "1" - an hour before enter the territory of the sender; • "24" - one day before enter the territory of the sender
shipmentRegister	No	boolean	Parameter determining the need to make an appointment by the driver of DL to pick-up the cargo at the sender's address. Default value: "false"
paidEntry	No	object	Parameter determining the need to pay the entry fee by the driver of DL when entering the territory of the sender to pick-up the cargo
— paidEntry.Cost	No	float	Amount, rub.
— paidEntry.Type	No	integer	Reimbursement method. Available values: <ul style="list-style-type: none"> • "1" - by the check at the address; • "2" - include in the bill
shipmentDerival	No	string	Parameter determining the need to provide the pick-up number by the driver of DL in order to pick-up the cargo at the sender's territory. Parameter should contain the pick-up number. Maximum number of characters - 30
priorCall	No	boolean	Parameter determining the need of advance call from the driver of DL to the sender before the picking-up of the cargo. Default value: "false"

noNeedAgreement	No	boolean	<p>Parameter determining the need to agree the order for shipment with the sender.</p> <p>Available values:</p> <ul style="list-style-type: none"> • "true" - not need to agree; • "false" - need to agree (default value)
documentsForReceive	No	array of string	<p>List of the documents that the driver of DL has to have in order to pick-up the cargo at the sender's territory. Should be specified using the "Documents for receipt of cargo" directory</p>

Address

Address

Parameter	Required	Type	Description
street	Yes	string	<p>CLADR code of the street. It's possible to get CLADR code using the services presented on the page "Using CLADR codes"</p>
house	Yes	string	<p>House.</p> <p>Maximum number of characters - 5</p>
building	No	string	<p>Building.</p> <p>Maximum number of characters - 5</p>
structure	No	string	<p>Structure.</p> <p>Maximum number of characters - 5</p>
flat	No	string	<p>Apartment/office.</p> <p>Maximum number of characters - 5</p>

Arrival

Arrival

Parameter	Required	Type	Description
variant	Yes	string	<p>Shipping method.</p> <p>Available values:</p> <ul style="list-style-type: none"> • "terminal" - delivery to the terminal; • "address" - delivery to the address. <p>If small-size cargo delivery is ordered ("delivery.deliveryType.type" request parameter value is "small"), then delivery to the terminal is not available</p>
payer	No	string	<p>Payer for the service.</p> <p>Available values:</p> <ul style="list-style-type: none"> • "sender"; • "receiver"; • "third" (third party). <p>If parameter is not passed, then it takes the value of the parameter "Request.Payment.primaryPayer"</p>

terminalID	Yes*	integer	<p>Terminal ID from the "Terminals" directory.</p> <p>*It is only possible to choose default terminal in this case (in Terminals directory "city.terminals.terminal.default" parameter value should be "true")</p> <p>If express delivery is ordered ("delivery.deliveryType.type" parameter value is "express"), the terminal should give out express cargoes (there should be "Worktables.Worktable.department" parameter with "Выдача грузов экспресс-перевозки" value for the selected terminal in Terminals directory).</p> <p>*It's possible to pass only one of parameters: "terminalID", "address", "city"</p>
address	Yes*	Address	<p>Address as a set of parameters.</p> <p>*It's possible to pass only one of parameters: "terminalID", "address", "city"</p>
city	Yes*	string	<p>CLADR code of the city. It's possible to get CLADR code using the services presented on the page "Using CLADR codes".</p> <p>*It's possible to pass only one of parameters: "terminalID", "address", "city"</p> <p>*This parameter is allowed to be passed if parameter "variant" has the value "terminal".</p> <p>When this parameter is passed the arrival terminal is determined automatically</p>
time	Yes*	object	<p>Time of cargo delivery.</p> <p>*Parameter is required only if specified shipping method is "address"</p>
— time.worktimeStart	Yes	string	<p>Beginning of period of cargo delivery.</p> <p>Format: HH:MM</p>
— time.worktimeEnd	Yes	string	<p>End of period of cargo delivery.</p> <p>Format: HH:MM</p>
— time.breakStart	No	string	<p>Beginning of the break.</p> <p>Format: HH:MM</p>
— time.breakEnd	No	string	<p>End of the break.</p> <p>Format: HH:MM</p>
— time.exactTime	No	boolean	<p>Delivery at the exact time.</p> <p>Default value: "false"</p>
handling	No	object	<p>Loading and unloading works at the address.</p> <p>Such works may be ordered in case of delivery to the address (parameter "variant" has the value "address")</p>
— handling.freightLift	No	boolean	<p>There is a freight elevator.</p> <p>Default value: "false"</p>
— handling.toFloor	No	integer	<p>Number of the floor to which the cargo is to be lifted.</p> <p>Maximum number of characters - 5</p>

— handling.carry	No	integer	The distance of carrying the load manually. Maximum number of characters - 5
— handling.payer	No	string	Payer for the service. Available values: <ul style="list-style-type: none"> • "sender"; • "receiver"; • "third" (third party). If parameter is not passed, then it takes the value of the parameter "Request.Payment.primaryPayer"
requirements	No	array of string	Array of UID's of special requirements for transport from the Directory of Special Requirements for Transport . Special requirements include type of truck loading (side, rear, etc.) and other requirements: manipulator, tenting removal, etc.

Requester

Requester

Parameter	Required	Type	Description
role	Yes	string	Role in shipping. Available values: <ul style="list-style-type: none"> • "sender"; • "receiver"; • "third" (third party)
email	Yes	string	E-mail of the order requester. Maximum number of characters - 128

Member

Member

Parameter	Required	Type	Description
counteragent	Yes	Counteragent	Counterparty as a set of parameters
contactPersons	Yes*	array of ContactPerson	Contact person. When the order is created from the public part, only one item in the "contactPersons" array can be passed. *Parameter is not required and ignored for counterparty that is an "anonymous" receiver (1)
phoneNumbers	Yes*	array of PhoneNumber	Phone number. When the order is created from the public part, only one item in the "phoneNumbers" array can be passed. *Parameter is not required and ignored for counterparty that is an "anonymous" receiver (1)

email	No	string	E-mail of the order requester. Maximum number of characters - 128
dataForReceipt	Yes*	DataForReceipt	Contact information for sending an electronic payment receipt to the payer that is a physical party *Parameter is required for the counterparty, that is a physical party and is not an "anonymous" receiver. Otherwise, parameter is not required and ignored (1)

Notes:

1. "Anonymous" receiver - a receiver on whom minimum info was provided.

Delovye Linii company allows providing minimum information on the receiver - only name and phone number. In this case SMS with a code is sent to the phone number. The code is used to receive the goods. For more information see the description of [Simplified Shipping](#) service on Delovye Linii company website

Counteragent

Counteragent			
Counteragent			
Parameter	Required	Type	Description
form	Yes*	integer	UID of legal form of organization. Value from the " Directory of legal forms of organization ". When passing data about the "anonymous" (1) receiver ("isAnonym" parameter value is "true") it is necessary to pass UID of individual in Russian Federation ("0xAB91FEEA04F6D4AD48DF42161B6C2E7A"). *It's possible to pass only one of parameters: "form", "customForm"
customForm	Yes*	object	Legal form of organization as a set of parameters. *It's possible to pass only one of parameters: "form", "customForm"
— customForm.formName	Yes	string	Name of legal form of organization. Maximum number of characters - 35
— customForm.countryUID	Yes	string	Country UID from the " Countries " directory
— customForm.juridical	Yes	boolean	Indicator of juridical party
document	Yes*	object	Personal identification document *Parameter is required only if both of parameters "customForm.juridical" and "isAnonym" are passed with the value "false"
— document.type	Yes	string	Document type. Available values: <ul style="list-style-type: none"> • "passport"; • "drivingLicence"; • "foreignPassport". The value "foreignPassport" is unavailable for some countries
— document.serial	Yes*	string	Serial of the document. *Parameter is not required and ignored for some countries

— document.number	Yes	string	Document number. Format depends on the country
isAnonym	No	boolean	Flag indicating that counterparty is an "anonymous" receiver, that is minimal information about the receiver is provided, this service is called simplified shipment (1). It's possible to pass this parameter with value "true" only for the receiver. Default value: "false"
phone	Yes*	string	Phone number of counterparty that is an "anonymous" receiver (1). Format: "7XXXXXXXXXX" (11 digits, starts with "7"). *Parameter is required only for counterparty that is an "anonymous" receiver
name	Yes	string	Name of counterparty
inn	Yes*	string	Counterparty TIN. Maximum number of characters depends on the country and legal form of organization *Parameter is required only for juridical party (parameter "form" has value that is an UID of legal form or organization of juridical party or "customForm.juridical" = "true")
juridicalAddress	No	Address	Juridical address. Parameter is used only for juridical party (parameter "form" has value that is an UID of legal form or organization of juridical party or "customForm.juridical" = "true")

Notes:

1. "Anonymous" receiver - a receiver on whom minimum info was provided.

Delovye Linii company allows providing minimum information on the receiver - only name and phone number. In this case SMS with a code is sent to the phone number. The code is used to receive the goods. For more information see the description of [Simplified Shipping](#) service on Delovye Linii company website

ContactPerson

ContactPerson

Parameter	Required	Type	Description
name	Yes	string	Name of contact person

PhoneNumber

PhoneNumber

Parameter	Required	Type	Description
number	Yes	string	Phone number. Maximum 15 digits
ext	No	string	Extension. Maximum 5 digits

DataForReceipt

DataForReceipt

Параметр	Required	Тип	Описание
send	Yes	boolean	<p>Consent to receive an electronic payment receipt. Available values:</p> <ul style="list-style-type: none"> • "true" - user passed "phone" and/or "email" to send payment receipt; • "false" - user refused to provide contact information to send payment receipt
phone	Yes*	string	<p>Phone number to send payment receipt.</p> <p>Format: "+79XXXXXXXX" (12 figures, starts with "+79" and then 9 digits)</p> <p>*If "send" = "true", than at least one of the parameters is required: "phone" or "email"</p> <p>*If "send" = "false", than parameter is ignored</p>
email	Yes*	string	<p>E-mail to send payment receipt</p> <p>*If "send" = "true", than at least one of the parameters is required: "phone" or "email"</p> <p>*If "send" = "false", than parameter is ignored</p>

Cargo

Cargo

Parameter	Required	Type	Description
quantity	No	integer	<p>Quantity of cargo pieces, pcs.</p> <p>Default value: "1".</p> <p>If delivery type is "letter" ("Request.Delivery.DeliveryType.type" = "letter"), then the passed value is ignored, parameter takes the default value ("1")</p>
length	Yes*	float	<p>Length of the longest cargo piece, m.</p> <p>*If delivery type is "letter" ("Request.Delivery.DeliveryType.type" = "letter"), then this parameter is not required, passed value is ignored, parameter takes the value "0.3"</p>
width	Yes*	float	<p>Width of the widest cargo piece, m.</p> <p>*If delivery type is "letter" ("Request.Delivery.DeliveryType.type" = "letter"), then this parameter is not required, passed value is ignored, parameter takes the value "0.21"</p>

height	Yes*	float	Height of the highest cargo piece, m. *If delivery type is "letter" ("Request.Delivery.DeliveryType.type" = "letter"), then this parameter is not required, passed value is ignored, parameter takes the value "0.01"
weight	No*	float	Weight of the heaviest cargo piece, kg. *If quantity of cargo pieces > 1 ("Request.Cargo.quantity" > 1), then this parameter is required. Otherwise, this parameter takes the value of the parameter "totalWeight". *If delivery type is "letter" ("Request.Delivery.DeliveryType.type" = "letter"), then this parameter is not required, passed value is ignored, parameter takes the value "0.5"
totalVolume	Yes*	float	Total cargo volume, cub. m. *If delivery type is "letter" ("Request.Delivery.DeliveryType.type" = "letter"), then this parameter is not required, passed value is ignored, parameter takes the value "0.001"
totalWeight	Yes*	float	Total cargo weight, kg. *If delivery type is "letter" ("Request.Delivery.DeliveryType.type" = "letter"), then this parameter is not required, passed value is ignored, parameter takes the value "0.5"
oversizedVolume	No*	float	Volume of oversized cargo places, cub. m (1). *If delivery type is "letter" ("Request.Delivery.DeliveryType.type" = "letter"), then this parameter is ignored. *If according to the weight-dimensional characteristics it is determined that the cargo is oversized, then this parameter is required
oversizedWeight	No*	float	Weight of oversized cargo places, kg (1). *If delivery type is "letter" ("Request.Delivery.DeliveryType.type" = "letter"), then this parameter is ignored. *If according to the weight-dimensional characteristics it is determined that the cargo is oversized, then this parameter is required
hazardClass	No	float	Hazard class of cargo. Default value: "0"
insurance	No	object	Information about cargo insurance
— insurance.statedValue	No	float	Declared value of the cargo, rub. Maximum number of characters - 12

— insurance.payer	No	string	<p>Payer for the service.</p> <p>Available values:</p> <ul style="list-style-type: none"> • "sender"; • "receiver"; • "third" (third party). <p>If parameter is not passed, then it takes the value of the parameter "Request.Payment.primaryPayer"</p>
— insurance.term	No	boolean	<p>Flag of insurance of delivery time.</p> <p>Default value: "true"</p>
freightName	Yes*	string	<p>Nature of cargo (textual value).</p> <p>*It's possible to pass only one of parameters: "freightName", "freightUID"</p>
freightUID	Yes*	string	<p>UID of nature of cargo from the "Nature of cargo" directory. To search for UID by the name of cargo use the Cargo Type by an Input String method.</p> <p>*It's possible to pass only one of parameters: "freightName", "freightUID"</p>

Notes:

1. An oversized cargo place is a cargo place with weight greater than or equal to 100 kg (80 kg in case of air transportation) or with at least one of the dimensions (LWH) greater than or equal to 3 m (80 cm in case of air transportation)

Method response

Response example

```
<response>
  <metadata>
    <status>200</status>
    <generated_at>2015-06-18 12:37:28</generated_at>
  </metadata>
  <data>
    <state>success</state>
    <requestID>3954004</requestID>
    <barcode>41508460D0905400400000014</barcode>
  </data>
</response>
```

Description of parameters

Response

Parameter	Type	Description
metadata	object	System information about the order
— metadata.status	integer	Emulated http-code of status. In case of success the code "200" returns
— metadata.generated_at	string	<p>Date and time of the server response generation.</p> <p>Format: "YYYY-MM-DD HH:MM:SS"</p>
data	Data	Information about the order

Data

Parameter	Type	Description
state	string	Request processing status
requestID	string	Number of created order or pre-order
barcode	string	Barcode according to algorithm Code 128 (for pre-order , that is in case "delivery.derival.variant" request parameter value is "terminal")

Error handling

Except for [common API errors](#) the method response may contain the following errors:

Error number	http-code	Error title		Error description	
		Title	Translation	Description	Translation
609013	400	Ошибка параметров оплаты	Payment parameters error	Детальное описание ошибки см. в поле "detail" ответа	Detailed error description see in the field "detail" of the response
609016	400	Ошибка при сохранении заявки	Saving order error	Невозможно сохранить заявку	Unable to save order