

Updating the order contact data

Обновлено 29.06.2020

Содержание:

- General information
- Updating the order contact data
 - Method request
 - Request example
 - Description of parameters
 - Request
 - Member
 - Method response
 - Response example
 - Description of parameters
 - Response
 - Error handling

General information

The service allows changing the sender and the receiver contact data (it is not possible to change the contact data of "anonymous" receiver, see below). It is only possible to change the contact information for orders that can be accessed from the current user account.



"Anonymous" receiver - a receiver on whom minimum info was provided. Delovye Linii company allows providing minimum information on the receiver - only name and phone number. In this case SMS with a code is sent to the phone number. The code is used to receive the goods. For more information see the description of [Simplified Shipping](#) service on Delovye Linii company website

Updating the order contact data

Method request

Request example

Method address: https://api.dellin.ru/v3/orders/change_contacts.xml

```
<request>
  <appkey>00000000-0000-0000-0000-000000000000</appkey>
  <sessionID>00000000-0000-0000-0000-000000000000</sessionID>
  <orderID>1900395024773</orderID>
  <members>
    <sender>
      <contactIDs>15637261</contactIDs>
      <contactIDs>15638153</contactIDs>
      <contactIDs>15638154</contactIDs>
      <phoneIDs>19501308</phoneIDs>
      <phoneIDs>19501311</phoneIDs>
      <phoneIDs>19501312</phoneIDs>
      <contactPersons>
        <name>senderContact1</name>
      </contactPersons>
      <contactPersons>
        <name>senderContact2</name>
      </contactPersons>
      <contactPersons>
        <name>senderContact3</name>
      </contactPersons>
      <phoneNumbers>
        <number>79620000000</number>
        <ext>3567</ext>
      </phoneNumbers>
      <phoneNumbers>
        <number>79510000000</number>
      </phoneNumbers>
      <phoneNumbers>
        <number>79500000000</number>
      </phoneNumbers>
    </sender>
    <receiver>
      <contactIDs>15638146</contactIDs>
      <phoneIDs>19501297</phoneIDs>
      <contactPersons>
        <name>receiverContact</name>
      </contactPersons>
      <phoneNumbers>
        <number>79520000000</number>
      </phoneNumbers>
    </receiver>
  </members>
</request>
```

Description of parameters

Request

Request			
Parameter	Required	Type	Description
appkey	Yes	string	Application key. To get the key, register
sessionID	Yes	string	Session ID. To get the session ID, use User authorization service.
orderID	Yes	string	Number of the order to be modified
members	Yes	object	Contact information to be modified. It is possible to transfer new contact data or update information already stored in the address book of the personal account
— members.sender	No	Member	Sender contact information to be modified
— members.receiver	No	Member	Receiver contact information to be modified

Member

Member			
Parameter	Required	Type	Description

contactIDs	No*	array of integer	<p>IDs of the contact persons from Address book.</p> <p>Maximum 3 elements in the array.</p> <p>*The parameter is not required and is ignored if the user is not authorized.</p> <p>*Only one of the following parameters can be passed in the request: contactIDs or contactPersons</p>
phoneIDs	No*	array of integer	<p>IDs of phone numbers from Address book.</p> <p>Maximum 3 elements in the array.</p> <p>*The parameter is not required and is ignored if the user is not authorized.</p> <p>*Only one of the following parameters can be passed in the request: phoneIDs or phoneNumbers</p>
contactPersons	No*	array of ContactPersons	<p>List of contact persons.</p> <p>Maximum 3 elements in the array.</p> <p>*Only one of the following parameters can be passed in the request: contactIDs or contactPersons</p>
— contactPersons.name	No	string	Contact person name
phoneNumbers	No*	array of PhoneNumbers	<p>List of phone numbers.</p> <p>Maximum 3 elements in the array.</p> <p>*Only one of the following parameters can be passed in the request: phoneIDs or phoneNumbers</p>
— phoneNumbers.number	No	string	<p>Contact person phone number</p> <p>Format: 79XXXXXXXX (11 characters starting with 7)</p>
— phoneNumbers.ext	No	string	Extension number. 4 characters maximum

Method response

Response example

```
<response>
  <metadata>
    <status>200</status>
    <generated_at>2019-11-18 12:52:26</generated_at>
  </metadata>
  <data>
    <status>success</status>
  </data>
</response>
```

Description of parameters

Response

Parameter	Type	Description
metadata	object	System information
— metadata.status	integer	Emulated status http-code. If successful, code 200 is returned. In case of error - 400
— metadata.generated_at	string	<p>Server response date and time.</p> <p>Format: YYYY-MM-DD HH:MM:SS</p>

data	object	Success confirmation
— data.status	string	Status in English. Possible value - "success"

Error handling

The common API errors are used with the method, for errors format description and errors list see [Errors of API methods](#).