

# Favorite orders

Обновлено 18.03.2021

## Содержание:

- [General information](#)
- [Favorite orders](#)
  - [Method request](#)
    - [Request example](#)
    - [Description of parameters](#)
      - [Request](#)
  - [Method response](#)
    - [Response example](#)
    - [Description of parameters](#)
      - [Response](#)
  - [Error handling](#)
- [Deleting order from favorites](#)
  - [Method request](#)
    - [Request example](#)
    - [Description of parameters](#)
      - [Request](#)
  - [Method response](#)
  - [Error handling](#)

## General information

The service allows adding orders to favorites and deleting orders from favorites.

## Favorite orders

### Method request

#### Request example

Method address: <https://api.dellin.ru/v2/favorites/add.xml>

```
<request>
  <appkey>00000000-0000-0000-0000-000000000000</appkey>
  <sessionId>00000000-0000-0000-0000-000000000000</sessionId>
  <orderid>345235</orderid>
</request>
```

#### Description of parameters

##### Request

##### Request

Parameter	Required	Type	Description
appkey	Yes	string	Application key. To get the key, <a href="#">register</a>
sessionId	Yes	string	To get the session ID, use the <a href="#">User Authorization</a> method
orderId	Yes	string	Number of the order that needs to be added to favorites

### Method response

#### Response example

```
<response>
  <metadata>
    <status>200</status>
    <generated_at>2020-04-01 07:47:32</generated_at>
  </metadata>
  <data>ok</data>
</response>
```

### Description of parameters

Response

#### Response

Parameter	Type	Description
metadata	object	System information
— metadata.status	integer	Emulated status http-code. If successful, code 200 is returned
— metadata.generated_at	string	Server response date and time. Format: YYYY-MM-DD HH:MM:SS
data	string	Request status. Possible value - "ok"

### Error handling

The common API errors are used with the method, for errors format description and errors list see [Errors of API methods](#).

## Deleting order from favorites

### Method request

#### Request example

Method address: <https://api.dellin.ru/v2/favorites/delete.xml>

```
<request>
  <appkey>00000000-0000-0000-0000-000000000000</appkey>
  <sessionid>00000000-0000-0000-0000-000000000000</sessionid>
  <orderid>345235</orderid>
</request>
```

### Description of parameters

Request

Parameter	Required	Type	Description
appkey	Yes	string	Application key. To get the key, <a href="#">register</a>
sessionID	Yes	string	To get the session ID, use the <a href="#">User Authorization</a> method
orderId	Yes	string	Number of the order that needs to be added to favorites

### Method response

✓ Response of the method "Deleting order from favorites" is similar to the response of the method "[Adding order to favorites](#)"

### Error handling

The common API errors are used with the method, for errors format description and errors list see [Errors of API methods](#).