

Changing the order receiver data

Обновлено 26.06.2020

Содержание:

- [General information](#)
- [Changing the order receiver data](#)
 - [Method request](#)
 - [Request example](#)
 - [Description of parameters](#)
 - [Request](#)
 - [Member](#)
 - [Counteragent](#)
 - [Method response](#)
 - [Response example](#)
 - [Description of parameters](#)
 - [Response](#)
 - [Error handling](#)

General information

The service allows changing the recipient for an already placed order, if necessary appointing the new recipient as the payer for the order, as well as determining who will incur the costs of the paid storage - the sender, the new recipient or a third party.

To check the possibility of changing the recipient, use [Checking possibility to change the order](#) method.



The storage of the arrived cargo is free of charge for the first two business days, starting from the third day it is necessary to pay for the cargo storage. For more information on conditions and prices see Delovye Linii company [website](#).

Changing the order receiver data

Method request

Request example

Method address: https://api.dellin.ru/v3/orders/change_receiver.xml

```
<request>
<appkey>00000000-0000-0000-0000-000000000000</appkey>
<sessionID>00000000-0000-0000-0000-000000000000</sessionID>
<orderID>00000000</orderID>
<receiver>
<counteragentID>456783515</counteragentID>
<counteragent>
<form>0x8F51001438C4D49511DBD774581EDB80</form>
<document>
<type>passport</type>
<serial>1111</serial>
<number>123456</number>
</document>
<inn>1234567890</inn>
<name>Помашка</name>
<juridicalAddress>
<street>780000000000438000000000</street>
<house>4</house>
<building>2</building>
<structure>3A</structure>
<flat>6-234</flat>
</juridicalAddress>
</counteragent>
<contactIDs>12345678</contactIDs>
<contactIDs>78456123</contactIDs>
<contactPersons>
<name>Иван Иванович</name>
</contactPersons>
<contactPersons>
<name>Петр Петрович</name>
</contactPersons>
<phoneIDs>98765412</phoneIDs>
<phoneIDs>65478921</phoneIDs>
<phoneNumbers>
<number>79213332211</number>
<ext>0123</ext>
</phoneNumbers>
<email>test@mail.ru</email>
<dataForReceipt>
<phone>+79999999999</phone>
<email>test@mail.ru</email>
</dataForReceipt>
</receiver>
<changeOrderPayer>true</changeOrderPayer>
<storePayer>third</storePayer>
<third>
<counteragentID>456783515</counteragentID>
<counteragent>
<form>0x8F51001438C4D49511DBD774581EDB80</form>
<document>
<type>passport</type>
<serial>1111</serial>
<number>123456</number>
</document>
<inn>1234567890</inn>
<name>Помашка</name>
<juridicalAddress>
<street>780000000000438000000000</street>
<house>4</house>
<building>2</building>
<structure>3A</structure>
<flat>6-234</flat>
</juridicalAddress>
</counteragent>
<contactIDs>12345678</contactIDs>
<contactIDs>78456123</contactIDs>
<contactPersons>
<name>Иван Иванович</name>
</contactPersons>
<contactPersons>
<name>Петр Петрович</name>
</contactPersons>
<phoneIDs>98765412</phoneIDs>
<phoneIDs>65478921</phoneIDs>
<phoneNumbers>
<number>79213332211</number>
<ext>0123</ext>
</phoneNumbers>
<email>test@mail.ru</email>
<dataForReceipt>
<phone>+79999999999</phone>
<email>test@mail.ru</email>
</dataForReceipt>
</third>
</request>
```

Description of parameters

Request

Request

Parameter	Required	Type	Description
appkey	Yes	string	Application key. To get the key, register
sessionID	Yes	string	Session ID. To get the session ID, use User authorization service
orderID	Yes	string	The number of the order for which it is necessary to change the receiver

receiver	Yes	Member	New receiver info
changeOrderPayer	Yes	boolean	<p>Flag indicating that it is necessary to change the payer.</p> <p>Possible values:</p> <ul style="list-style-type: none"> • "true" - change the payer to the new receiver; • "false" - do not change the payer
storePayer	Yes	string	<p>Party that incurs the cost of paid storage.</p> <p>Possible values:</p> <ul style="list-style-type: none"> • "sender"; • "receiver"; • "third" - third party. If the parameter is passed in the request, the "third" is required
third	No*	Member	<p>Third party info.</p> <p>*If "storePayer" parameter value is "third" then the parameter "third" is required</p>
Member			
Member			
Parameter	Required	Type	Description
counteragentID	No*	integer	<p>Counterparty ID from address book.</p> <p>*One of the following excluding parameters is required: "counteragentID" or "counteragent"</p>
counteragent	No*	Counteragent	<p>Counterparty info</p> <p>*One of the following excluding parameters is required: "counteragentID" or "counteragent"</p>
contactIDs	No*	array of integers	<p>Contact persons IDs from address book.</p> <p>Maximum 3 elements in the array.</p> <p>*One of the following excluding parameters is required: "contactIDs" or "contactPersons"</p>
contactPersons	No*	array of contactPersons	<p>Contact persons data.</p> <p>Maximum 3 elements in the array.</p> <p>*One of the following excluding parameters is required: "contactIDs" or "contactPersons"</p>
contactPersons.name	Yes	string	Contact person name
phoneIDs	No*	array of integers	<p>Phone number IDs from address book.</p> <p>Maximum 3 elements in the array.</p> <p>*One of the following excluding parameters is required: "phoneIDs" or "phoneNumbers"</p>

phoneNumbers	No*	array of phoneNumbers	Phone numbers list. Maximum 3 elements in the array. *One of the following excluding parameters is required: "phoneIDs" or "phoneNumbers"
phoneNumbers.number	Yes	string	Phone number. 15 digits maximum
phoneNumbers.ext	No	string	Extension phone number. 5 digits maximum
email	No	string	Ordering customer email. 128 characters maximum
dataForReceipt	No	object	Contact data to send the payment receipt to the individual. The parameter is used in the following cases: <ul style="list-style-type: none"> 1. The new receiver is an individual and is going to be the payer ("changeOrderPayer" parameter values is "true", individual UID is passed as "receiver.counteragent.form" parameter value). 2. The payer that incurs the costs of the paid storage is neither sender, nor receiver ("storePayer" parameter values is "third", individual UID is passed as "third.counteragent.form" parameter value).

— dataForReceipt.phone	No*	string	Phone number for sending the payment receipt, required format: "+79XXXXXXXX" (where X is any digit). *At least one of the following parameters is required: "dataForReceipt.phone", "dataForReceipt.email"
— dataForReceipt.email	No*	string	Email address for sending the payment receipt. 128 characters maximum *At least one of the following parameters is required: "dataForReceipt.phone", "dataForReceipt.email"

Counteragent

Counteragent			
Parameter	Required	Type	Description
form	Yes	string	UID of legal form of organization from the Directory of legal forms of organization

document	No*	object	<p>Personal ID data. The parameter is used only for individuals (that is when an individual UID is passed in the "form" parameter).</p> <p>*If the counterparty is an individual, the parameter is required</p>
document.type	Yes	string	<p>Document type.</p> <p>Possible values:</p> <ul style="list-style-type: none"> • "passport"; • "drivingLicence"; • "foreignPassport" <ul style="list-style-type: none"> - international passport. For some countries "foreignPassport" value is not available
document.serial	Yes*	string	<p>Document series</p> <p>*For some countries the parameter is not required and therefore ignored</p>
document.number	Yes	string	<p>Document number. Number format may vary depending on the country</p>
inn	No*	integer	<p>TIN (taxpayer identification number). Allowed number of characters may vary depending on country and legal form of organization. The parameter is used for legal entities only (that is when legal entity UID is passed in the "form" parameter).</p> <p>*If the counterparty is a legal entity, the parameter is required</p>
name	Yes	string	<p>Individual or company name</p>
juridicalAddress	No*	object	<p>Legal address. The parameter is used for legal entities only (that is when legal entity UID is passed in the "form" parameter).</p> <p>*If the counterparty is a legal entity, the parameter is required</p>
juridicalAddress.street	Yes	string	<p>CLADR* code of the street (see. "Streets directory").</p> <p>*CLADR - Classifier of Addresses of Russian Federation</p>
juridicalAddress.house	Yes	string	<p>House number, including the letter. For example, "13/A"</p>
juridicalAddress.building	No	string	<p>Building</p>
juridicalAddress.structure	No	string	<p>Structure</p>
juridicalAddress.flat	No	string	<p>Apartment/office, including the letter. For example, "222 A"</p>

Method response

Response example

```
<response>
  <metadata>
    <status>200</status>
    <generated_at>2019-11-18 12:52:26</generated_at>
  </metadata>
  <data>
    <status>success</status>
  </data>
</response>
```

Description of parameters

Response

Response

Parameter	Type	Description
metadata	object	System information
— metadata.status	integer	Emulated status http-code. If successful, code 200 is returned. In case of error - 400
— metadata.generated_at	string	Server response date and time. Format: YYYY-MM-DD HH:MM:SS
data	object	Success confirmation
— data.status	string	Status in English. Possible value - "success"

Error handling

Except for [common API errors](#) the method response may contain the following errors:

Error number	http-code	Error title		Error description	
		Title	Translation	Description	Translation
610001	400	По данному заказу изменение получателя недоступно	The receiver for the order can not be changed	-	-
610002	400	По данному заказу изменение получателя недоступно	The receiver for the order can not be changed	Изменение по данному заказу недоступно в связи с отсутствием доступа	It is not possible to change the order details since there is no access
610003	400	Указан анонимный контрагент	"Anonymous" counteragent indicated	Данная операция невозможна для контрагента анонима	The operation is not available for an "anonymous" counteragent