

Suspension and resumption of the cargo delivery

Обновлено 20.05.2022

Содержание:

- [General information](#)
- [Delivery suspension](#)
 - [Method request](#)
 - [Request structure](#)
 - [Description of parameters](#)
 - [Request](#)
 - [Method response](#)
 - [Response structure](#)
 - [Description of parameters](#)
 - [Response](#)
 - [Error handling](#)
- [Delivery resumption](#)
 - [Method request](#)
 - [Request structure](#)
 - [Description of parameters](#)
 - [Request](#)
 - [Method response](#)
 - [Error handling](#)

General information

This service allows suspending as well as resuming delivery. To suspend/resume the delivery full access to the sender is required (for more information on full access see "[Available counterparties](#)" method, the description of info.accessLevel parameter). To check the possibility of changing, use "[Checking possibility to change the order](#)" method. The changes do not come into effect immediately. To check the change request status use "[Change history](#)" method.

Delivery suspension

Method request

Request structure

Method address: <https://api.dellin.ru/v3/orders/suspend.json>

```
{
  "appkey": "00000000-0000-0000-0000-000000000000",
  "sessionID": "00000000-0000-0000-0000-000000000000",
  "orderID": "345235",
  "suspendDate": "2018-05-31"
}
```

Description of parameters

Request

Request

Parameter	Required	Type	Description
appkey	Yes	string	Application key. To get the key, register
sessionID	Yes	string	To get the session ID, use the User Authorization method
orderID	Yes	string	ID of the order to be suspended
suspendDate	Yes	string	Suspension end date

Method response


Response structure

```
{
  "metadata": {
    "status": 200,
    "generated_at": "2015-06-18 12:37:28"
  },
  "data": {
    "state": "success"
  }
}
```

Description of parameters

Response

Response

Parameter	Type	Description
metadata	object	System information
— metadata.status	integer	Emulated status http-code. If successful, code 200 is returned
— metadata.generated_at	string	Server response date and time. Format: YYYY-MM-DD HH:MM:SS
data	object	Success confirmation
<div> "Success" status indicates that the request was accepted. To check the change request status use "Change history" method</div>		
— data.state	string	Request status. Possible value - "success"

Error handling

Except for [common API errors](#) the method response may contain the following errors:

Error number	http-code	Error title	
		Title	Translation
608001	400	Заказ не найден	Order not found
608002	400	Операция недоступна	Operation unavailable
608003	400	Некорректная дата	Incorrect date

Delivery resumption

Method request

Request structure

Method address: <https://api.dellin.ru/v3/orders/resume.json>

```
{
  "appkey": "00000000-0000-0000-0000-000000000000",
  "sessionID": "00000000-0000-0000-0000-000000000000",
  "orderId": "345235",
  "resumeDate": "2018-05-25"
}
```

Description of parameters

Request

Parameter	Required	Type	Description
appkey	Yes	string	Application key. To get the key, register

sessionID	Yes	string	To get the session ID, use the User Authorization method
orderId	Yes	string	ID of the order to be resumed
resumeDate	Yes	string	Delivery resumption date

Method response

- ✓ Response of the method "Delivery resumption" is similar to the response of the method "[Delivery suspension](#)".

Error handling

- ✓ Errors of the method "Delivery resumption" are similar to the errors of the method "[Delivery suspension](#)".