

Suspension and resumption of the cargo delivery

Обновлено 20.05.2022

Содержание:

- [General information](#)
- [Delivery suspension](#)
 - [Method request](#)
 - [Request structure](#)
 - [Description of parameters](#)
 - [Request](#)
 - [Method response](#)
 - [Response structure](#)
 - [Description of parameters](#)
 - [Response](#)
 - [Error handling](#)
- [Delivery resumption](#)
 - [Method request](#)
 - [Request structure](#)
 - [Description of parameters](#)
 - [Request](#)
 - [Method response](#)
 - [Error handling](#)

General information

This service allows suspending as well as resuming delivery. To suspend/resume the delivery full access to the sender is required (for more information on full access see "[Available counterparties](#)" method, the description of info.accessLevel parameter). To check the possibility of changing, use "[Checking possibility to change the order](#)" method. The changes do not come into effect immediately. To check the change request status use "[Change history](#)" method.

Delivery suspension

Method request

Request structure

Method address: <https://api.dellin.ru/v3/orders/suspend.json>

```
{
  "appkey": "00000000-0000-0000-0000-000000000000",
  "sessionID": "00000000-0000-0000-0000-000000000000",
  "orderID": "345235",
  "suspendDate": "2018-05-31"
}
```

Description of parameters

Request

Request

| Parameter | Required | Type | Description |
|-------------|----------|--------|--|
| appkey | Yes | string | Application key. To get the key, register |
| sessionID | Yes | string | To get the session ID, use the User Authorization method |
| orderID | Yes | string | ID of the order to be suspended |
| suspendDate | Yes | string | Suspension end date |

Method response


Response structure

```
{
  "metadata":{
    "status":200,
    "generated_at":"2015-06-18 12:37:28"
  },
  "data":{
    "state":"success"
  }
}
```

Description of parameters

Response

Response

| Parameter | Type | Description |
|--|---------|--|
| metadata | object | System information |
| — metadata.status | integer | Emulated status http-code. If successful, code 200 is returned |
| — metadata.generated_at | string | Server response date and time. Format: YYYY-MM-DD HH:MM:SS |
| data | object | Success confirmation |
| <div> "Success" status indicates that the request was accepted. To check the change request status use "Change history" method</div> | | |
| — data.state | string | Request status. Possible value - "success" |

Error handling

Except for [common API errors](#) the method response may contain the following errors:

| Error number | http-code | Error title | |
|--------------|-----------|---------------------|-----------------------|
| | | Title | Translation |
| 608001 | 400 | Заказ не найден | Order not found |
| 608002 | 400 | Операция недоступна | Operation unavailable |
| 608003 | 400 | Некорректная дата | Incorrect date |

Delivery resumption

Method request

Request structure

Method address: <https://api.dellin.ru/v3/orders/resume.json>

```
{
  "appkey":"00000000-0000-0000-0000-000000000000",
  "sessionID":"00000000-0000-0000-0000-000000000000",
  "orderId":"345235",
  "resumeDate":"2018-05-25"
}
```

Description of parameters

Request

| Parameter | Required | Type | Description |
|-----------|----------|--------|---|
| appkey | Yes | string | Application key. To get the key, register |

| | | | |
|------------|-----|--------|--|
| sessionID | Yes | string | To get the session ID, use the User Authorization method |
| orderId | Yes | string | ID of the order to be resumed |
| resumeDate | Yes | string | Delivery resumption date |

Method response

- ✓ Response of the method "Delivery resumption" is similar to the response of the method "[Delivery suspension](#)".

Error handling

- ✓ Errors of the method "Delivery resumption" are similar to the errors of the method "[Delivery suspension](#)".