

Favorite orders

Обновлено 19.01.2022

Содержание:

- [General information](#)
- [Favorite orders](#)
 - [Method request](#)
 - [Request structure](#)
 - [Description of parameters](#)
 - [Request](#)
 - [Method response](#)
 - [Response structure](#)
 - [Description of parameters](#)
 - [Response](#)
 - [Error handling](#)
- [Deleting order from favorites](#)
 - [Method request](#)
 - [Request structure](#)
 - [Description of parameters](#)
 - [Request](#)
 - [Method response](#)
 - [Error handling](#)

General information

The service allows adding orders to favorites and deleting orders from favorites.

Favorite orders

Method request

Request structure

Method address: <https://api.dellin.ru/v2/favorites/add.json>

```
{
  "appkey": "00000000-0000-0000-0000-000000000000",
  "sessionID": "00000000-0000-0000-0000-000000000000",
  "orderID": "345235"
}
```

Description of parameters

Request

Request

| Parameter | Required | Type | Description |
|-----------|----------|--------|--|
| appkey | Yes | string | Application key. To get the key, register |
| sessionID | Yes | string | To get the session ID, use the User Authorization method |
| orderID | Yes | string | Number of the order that needs to be added to favorites |

Method response

Response structure

```
{
  "metadata": {
    "status": 200,
    "generated_at": "2020-04-01 07:47:32"
  },
  "data": "ok"
}
```

Description of parameters

Response

Response

| Parameter | Type | Description |
|-------------------------|---------|--|
| metadata | object | System information |
| — metadata.status | integer | Emulated status http-code. If successful, code 200 is returned |
| — metadata.generated_at | string | Server response date and time. Format: YYYY-MM-DD HH:MM:SS |
| data | string | Request status. Possible value - "ok" |

Error handling

The common API errors are used with the method, for errors format description and errors list see [Errors of API methods](#).

Deleting order from favorites

Method request

Request structure

Method address: <https://api.dellin.ru/v2/favorites/delete.json>

```
{
  "appkey": "00000000-0000-0000-0000-000000000000",
  "sessionID": "00000000-0000-0000-0000-000000000000",
  "orderID": "345235"
}
```

Description of parameters

Request

| Parameter | Required | Type | Description |
|-----------|----------|--------|--|
| appkey | Yes | string | Application key. To get the key, register |
| sessionID | Yes | string | To get the session ID, use the User Authorization method |
| orderID | Yes | string | Number of the order that needs to be added to favorites |

Method response



Response of the method "Deleting order from favorites" is similar to the response of the method ["Adding order to favorites"](#)

Error handling

The common API errors are used with the method, for errors format description and errors list see [Errors of API methods](#).