

Deleting objects from address book

Обновлено 18.01.2022

Содержание:

- [General information](#)
- [Deleting of objects from the address book](#)
 - [Method request](#)
 - [Request structure](#)
 - [Description of parameters](#)
 - [Request](#)
 - [Method response](#)
 - [Response structure](#)
 - [Description of parameters](#)
 - [Response](#)
 - [Deleted](#)
 - [Error handling](#)

General information

This service allows deleting counterparties, addresses, contact persons and phones from the address book.

Deleting of objects from the address book

Method request

Request structure

Method address: <https://api.dellin.ru/v2/book/delete.xml>

```
<request>
  <appkey>00000000-0000-0000-0000-000000000000</appkey>
  <sessionID>00000000-0000-0000-0000-000000000000</sessionID>
  <counteragentIDs>123</counteragentIDs>
  <counteragentIDs>345</counteragentIDs>
  <addressIDs>3</addressIDs>
  <addressIDs>2</addressIDs>
  <addressIDs>1</addressIDs>
  <phoneIDs>1</phoneIDs>
  <phoneIDs>2</phoneIDs>
  <contactIDs>1</contactIDs>
  <contactIDs>2</contactIDs>
  <contactIDs>3</contactIDs>
</request>
```

Description of parameters

Request

Request

Parameter	Required	Type	Description
appkey	Yes	string	Application key. To get the key, register
sessionID	Yes	string	To get the session ID, use the User Authorization method
counteragentIDs	No	array of integers	Array of ID's of counterparties that need to be deleted
addressIDs	No	array of integers	Array of ID's of addresses that need to be deleted
phoneIDs	No	array of integers	Array of ID's of phone numbers that need to be deleted
contactIDs	No	array of integers	Array of ID's of contact persons that need to be deleted

Method response

Response structure

```
<response>
  <metadata>
    <status>200</status>
    <generated_at>2015-06-18 12:37:28</generated_at>
  </metadata>
  <data>
    <deleted>
      <counteragentIDs>123</counteragentIDs>
      <addressIDs>3</addressIDs>
      <addressIDs>2</addressIDs>
      <addressIDs>1</addressIDs>
      <contactIDs>1</contactIDs>
      <contactIDs>2</contactIDs>
      <contactIDs>3</contactIDs>
      <phoneIDs>1</phoneIDs>
      <phoneIDs>2</phoneIDs>
    </deleted>
    <notDeleted>
      <counteragentIDs>123</counteragentIDs>
      <addressIDs>6</addressIDs>
      <addressIDs>5</addressIDs>
      <addressIDs>4</addressIDs>
      <contactIDs>4</contactIDs>
      <contactIDs>5</contactIDs>
      <contactIDs>6</contactIDs>
      <phoneIDs>3</phoneIDs>
      <phoneIDs>4</phoneIDs>
    </notDeleted>
  </data>
</response>
```

Description of parameters

Response

Response

Параметр	Тип	Описание
metadata	object	System information
— metadata.status	string	Emulated status http-code. If successful, code 200 is returned
— metadata.generated_at	string	Server response date and time. Format: YYYY-MM-DD HH:MM:SS
data	object	Information on objects to be deleted from address book
— data.deleted	Deleted	The list of objects that has been deleted from address book
— data.notDeleted	Deleted	The list of objects that has <i>not</i> been deleted from address book (since there is no object with the forwarded ID)

Deleted

Deleted

Parameter	Type	Description
counteragentIDs	array of integers	Array of counterparties ID's
addressIDs	array of integers	Array of addresses ID's
contactIDs	array of integers	Array of contact persons ID's
phoneIDs	array of integers	Array of phone numbers ID's

Error handling

The common API errors are used with the method, for errors format description and errors list see [Errors of API methods](#).