

# Terminals for the selected location

Обновлено 04.10.2021

## Содержание:

- [General information](#)
- [Terminals search](#)
  - [Method request](#)
    - [Request example](#)
    - [Description of parameters](#)
      - [Request](#)
  - [Method response](#)
    - [Response example](#)
    - [Description of parameters](#)
      - [Response](#)

## General information

The service allows receiving the list of terminals for the selected city. To get the data of all the terminals use "[Terminals directory](#)" method.

## Terminals search

### Method request

#### Request example

Method address: [https://api.dellin.ru/v1/public/request\\_terminals.json](https://api.dellin.ru/v1/public/request_terminals.json)

```
{
  "appkey": "00000000-0000-0000-0000-000000000000",
  "sessionID": "00000000-0000-0000-0000-000000000000",
  "code": "780000000000000000000000",
  "cityid": "2423",
  "direction": "derival"
}
```

#### Description of parameters

##### Request

##### Request

Parameter	Required	Type	Description
appkey	Yes	string	Application key. To get the key, <a href="#">register</a>
sessionID	No	string	To get the session ID, use the " <a href="#">User Authorization</a> " method
code	No*	string	City CLADR code (1). See " <a href="#">CLADR search</a> " page.  *One of the excluding parameters must be passed in the request: "code" or "cityID"
cityID	No*	integer	City ID, see " <a href="#">Places search</a> ".  *One of the excluding parameters must be passed in the request: "code" or "cityID"
direction	No	string	Terminals function.  Possible values: <ul style="list-style-type: none"><li>• "derival" - accepting the cargo;</li><li>• "arrival" - giving out the cargo</li></ul>

**Note:**  
1. CLADR - Classifier of Addresses of Russian Federation

Method response

Response example

```
{
  "terminals": [
    {
      "id": 1,
      "city": "Санкт-Петербург",
      "cityID": 1,
      "city_code": "7800000000000000000000",
      "name": "Санкт-Петербург-Парнас",
      "address": "Санкт-Петербург, 1-й Верхний пер, дом № 12, литера Б",
      "default": true,
      "express": true
    }
  ]
}
```

Description of parameters

Response

Response

Parameter	Type	Description
terminals	array of Terminals	<p>The list of terminals located in the city and in the nearest locations (if any).</p> <p>If there are no terminals in the indicated city, the list of the terminals for the nearest location is provided.</p> <p>The list is not ordered - the terminals are listed in accordance with their order in DB</p>
— terminals.id	integer	Terminal ID from "Terminals" directory
— terminals.city	string	Terminal city
— terminals.cityID	integer	Terminal city ID, see "Places search"
— terminals.city_code	string	Terminal city CLADR (1) code
— terminals.name	string	Terminal name
— terminals.address	string	Terminal address
— terminals.default	boolean	Flag indicating that the terminal is the default city terminal. Each location present in the response has one default terminal
— terminals.express	boolean	Flag indicating that the terminal accepts express cargoes

**Notes:**  
1. CLADR - Classifier of Addresses of Russian Federation