

# Terminals for the selected location

Обновлено 04.10.2021

## Содержание:

- [General information](#)
- [Terminals search](#)
  - [Method request](#)
    - [Request example](#)
    - [Description of parameters](#)
      - [Request](#)
  - [Method response](#)
    - [Response example](#)
    - [Description of parameters](#)
      - [Response](#)

## General information

The service allows receiving the list of terminals for the selected city. To get the data of all the terminals use "[Terminals directory](#)" method.

## Terminals search

### Method request

#### Request example

Method address: [https://api.dellin.ru/v1/public/request\\_terminals.xml](https://api.dellin.ru/v1/public/request_terminals.xml)

```
<request>
  <apikey>00000000-0000-0000-0000-000000000000</apikey>
  <sessionID>00000000-0000-0000-0000-000000000000</sessionID>
  <code>780000000000000000000000</code>
  <cityid>2423</cityid>
  <direction>derival</direction>
</request>
```

#### Description of parameters

##### Request

##### Request

Parameter	Required	Type	Description
apikey	Yes	string	Application key. To get the key, <a href="#">register</a>
sessionID	No	string	To get the session ID, use the " <a href="#">User Authorization</a> " method
code	No*	string	City CLADR code (1). See " <a href="#">CLADR search</a> " page.  *One of the excluding parameters must be passed in the request: "code" or "cityID"
cityID	No*	integer	City ID, see " <a href="#">Places search</a> ".  *One of the excluding parameters must be passed in the request: "code" or "cityID"
direction	No	string	Terminals function.  Possible values: <ul style="list-style-type: none"><li>• "derival" - accepting the cargo;</li><li>• "arrival" - giving out the cargo</li></ul>

**Note:**  
1. CLADR - Classifier of Addresses of Russian Federation

Method response

Response example

```
<response>
  <terminals>
    <id>1</id>
    <city>Санкт-Петербург</city>
    <cityID>1</cityID>
    <city_code>780000000000000000000000</city_code>
    <name>Санкт-Петербург-Парнас</name>
    <address>Санкт-Петербург, 1-й Верхний пер, дом № 12, литера Б</address>
    <default>true</default>
    <express>true</express>
  </terminals>
</response>
```

Description of parameters

Response

Response

Parameter	Type	Description
terminals	array of Terminals	<p>The list of terminals located in the city and in the nearest locations (if any).</p> <p>If there are no terminals in the indicated city, the list of the terminals for the nearest location is provided.</p> <p>The list is not ordered - the terminals are listed in accordance with their order in DB</p>
— terminals.id	integer	Terminal ID from "Terminals" directory
— terminals.city	string	Terminal city
— terminals.cityID	integer	Terminal city ID, see "Places search"
— terminals.city_code	string	Terminal city CLADR (1) code
— terminals.name	string	Terminal name
— terminals.address	string	Terminal address
— terminals.default	boolean	Flag indicating that the terminal is the default city terminal. Each location present in the response has one default terminal
— terminals.express	boolean	Flag indicating that the terminal accepts express cargoes

**Notes:**  
1. CLADR - Classifier of Addresses of Russian Federation